Bohnenkamp

Moving Professionals

BKT



Hints and features:

REIFEN 23.5 R 25 195 A2 / 185 B, TL, EARTHMAX SR 41 L4* / E4**, CUT RESISTANT, DEMO 95%, UNRUNDER LAUF

Product-No.: 72300171

Technical Information:

Tyre size	23.5 R 25
TL/TT	TL
LI / SI	195 A2 / 185 B
Tread	Earthmax SR 41
Manufacturer	ВКТ
Specification	L4/E4, */**, C.R.
Recom. Rim	19.50/2.5
Width [mm]	615
Outer diameter [mm]	1611
Static radius [mm]	725
Rolling circumference [mm]	4.790
Payload in kg at kph (1)	12150 / 10
Payload in kg at kph (2)	9250 / 50
Inflation pressure [bar]	5,00
Weight [Kg]	382,05
Stud height [mm]	53,0
Zulassung	nicht notwendig
Star Rating	* **
TRA Code	L4, E4

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.