

**VREDESTEIN**  
TYRES



REIFEN VF 650 / 65 R 38 NRO  
169 D, TL, TRAXION OPTIMALL  
ECE106

**Product-No.: 10001393**

#### Technical Information:

Tyre size	VF 650 / 65 R 38 NRO
TL / TT	TL
LI / SI	169 D
Tread	TRAXION OPTIMALL
Manufacturer	Vredestein
Recom. Rim	DW23B
Permissible rim	DW20B
Width [mm]	665
Outer diameter [mm]	1.835
Static radius [mm]	800
Rolling circumference [mm]	5400
Payload in kg at kph (1)	5800 / 65
Inflation pressure [bar]	2,00
Weight [Kg]	253,60
Zulassung	ECE 106
NRO	NRO
Tyre technology	VF
Direction bound	Yes

#### Hints and features:

- The Vredestein Traxion Optimall is a new VF tyre for high-performance tractors
- Its extremely flexible casing design enables a reduction of the inflation pressure by up to 25 percent for low soil compaction
- The upper bead zone is reinforced for good stability even at low inflation pressure
- The strong lug end in the tread centre provides stability, low tread wear and good self-cleaning properties
- In on-road use, the tread with a high amount of rubber grants low wear and a long service lifespan
- The rounded tread contour enables good driving comfort