

VREDESTEIN
TYRES



REIFEN VF 710 / 70 R 38
181 D, TL, TRAXION OPTIMALL
ECE106

Product-No.: 10001397

Technical Information:

Tyre size	VF 710 / 70 R 38
TL / TT	TL
LI / SI	181 D
Tread	TRAXION OPTIMALL
Manufacturer	Vredestein
Recom. Rim	DW25B
Permissible rim	DW23B
Width [mm]	730
Outer diameter [mm]	1.945
Static radius [mm]	840
Rolling circumference [mm]	5760
Payload in kg at kph (1)	8250 / 65
Inflation pressure [bar]	2,00
Weight [Kg]	326,30
Tyre content 75% [litre]	865
Stud height [mm]	61,0
Zulassung	ECE 106
Tyre technology	VF
Direction bound	Yes

Hints and features:

- The Vredestein Traxion Optimall is a new VF tyre for high-performance tractors
- Its extremely flexible casing design enables a reduction of the inflation pressure by up to 25 percent for low soil compaction
- The upper bead zone is reinforced for good stability even at low inflation pressure
- The strong lug end in the tread centre provides stability, low tread wear and good self-cleaning properties
- In on-road use, the tread with a high amount of rubber grants low wear and a long service lifespan
- The rounded tread contour enables good driving comfort