



REIFEN VF 650 / 60 R 38
173 D, TL, AGRIFLEX 372 +
STEEL BELTED, ECE106

Product-No.: 10001573

Technical Information:

Tyre size	VF 650 / 60 R 38
TL / TT	TL
LI / SI	173 D
Tread	Agriflex 372 +
Manufacturer	Alliance
Specification	Steel Belted
Recom. Rim	DW23B
Permissible rim	DW21B
Width [mm]	650
Outer diameter [mm]	1.745
Static radius [mm]	780,6
Rolling circumference [mm]	5128
Payload in kg at kph (1)	6500 / 65
Inflation pressure [bar]	2,40
Weight [Kg]	247,60
Tyre content 75% [litre]	518,47
Stud height [mm]	58,0
Number of studs	20x2
Zulassung	ECE 106
Tyre technology	VF
Direction bound	Yes

Hints and features:

- The Alliance 372+ is a VF tyre for high performance tractors from approx. 220 hp
- Its extremely flexible sidewalls enable it to carry up to 40% more load capacity at the same inflation pressure or the same load capacity at 40% lower inflation pressure compared with a standard tyre
- The larger contact area provides excellent traction and consequently reduced fuel costs
- At the same time, soil compaction is reduced and the soil is optimally protected
- The R-1W tread pattern ensures excellent grip and a long service life
- The tyre can be used for cyclic field operation (CFO) on harvesters