



REIFEN VF 540 / 65 R 38
162 D, TL, AGRIFLEX 372 +
STEEL BELTED, ECE106

Product-No.: 10001574

Technical Information:

Tyre size	VF 540 / 65 R 38
TL / TT	TL
LI / SI	162 D
Tread	Agriflex 372 +
Manufacturer	Alliance
Specification	Steel Belted
Recom. Rim	DW20B
Permissible rim	DW18L, DW16L
Width [mm]	549
Outer diameter [mm]	1.667
Static radius [mm]	752,9
Rolling circumference [mm]	4951
Payload in kg at kph (1)	4750 / 65
Inflation pressure [bar]	2,00
Weight [Kg]	183,8
Tyre content 75% [litre]	384,67
Stud height [mm]	51,0
Number of studs	22x2
Zulassung	ECE 106
Tyre technology	VF
Direction bound	Yes

Hints and features:

- The Alliance 372+ is a VF tyre for high performance tractors from approx. 220 hp
- Its extremely flexible sidewalls enable it to carry up to 40% more load capacity at the same inflation pressure or the same load capacity at 40% lower inflation pressure compared with a standard tyre
- The larger contact area provides excellent traction and consequently reduced fuel costs
- At the same time, soil compaction is reduced and the soil is optimally protected
- The R-1W tread pattern ensures excellent grip and a long service life
- The tyre can be used for cyclic field operation (CFO) on harvesters