





Hints and features:

- The BKT FL 695 is a flotation radial tyre for trailers in construction and transport applications
- Its special tread pattern with center tread blocks grants a very good selfcleaning
- The strong casing enables excellent stability and high load capacities under all ground conditions
- Multiple steel cord layers protect the tyre against damages

REIFEN 600 / 60 R 30.5 179 D, TL, FL 695 STEEL BELTED, ECE106

Product-No.: 10001706

## **Technical Information:**

Tyre size	600 / 60 R 30.5
TL / TT	TL
LI/SI	179 D
Tread	FL 695
Manufacturer	BKT
Specification	Steel Belted
Recom. Rim	AG20.00
Width [mm]	611
Outer diameter [mm]	1.495
Static radius [mm]	693
Rolling circumference [mm]	4586
Payload in kg at kph (1)	7750 / 65
Inflation pressure [bar]	6,00
Weight [Kg]	223
Stud height [mm]	26,5
Zulassung	ECE 106
Direction bound	Yes
Weight [Kg] Stud height [mm] Zulassung	223 26,5 ECE 106

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.