



Hints and features:

REIFEN 520 / 85 R 42
168 A8 / 165 D, TL, 385, ECE106
(20.8 R 42) HIGH SPEED, DEMO 90%,
HÖHENSCHLAG

Product-No.: 72300322

Technical Information:

| | |
|----------------------------|----------------|
| Tyre size | 520 / 85 R 42 |
| TL / TT | TL |
| LI / SI | 168 A8 / 165 D |
| Tread | 385 |
| Manufacturer | Alliance |
| Specification | High Speed |
| Recom. Rim | 18 |
| Width [mm] | 538 |
| Outer diameter [mm] | 1956 |
| Static radius [mm] | 885 |
| Rolling circumference [mm] | 5.780 |
| Payload in kg at kph (1) | 5600 / 40 |
| Payload in kg at kph (2) | 5150 / 65 |
| Inflation pressure [bar] | 2,80 |
| Weight [Kg] | 202,76 |
| Tyre content 75% [litre] | 531 |
| Zulassung | ECE 106 |
| Direction bound | Yes |

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.