





Hints and features:

REIFEN VF 480 / 80 R 50 179 D, TL, AGRIMAX SPARGO ECE106, 1 STOLLEN BESCHÄDIGT

Product-No.: 72300383

Technical Information:

Tyre size	VF 480 / 80 R 50
TL/TT	TL
LI/SI	179 D
Tread	Agrimax Spargo
Manufacturer	BKT
Recom. Rim	16
Permissible rim	15
Width [mm]	479
Outer diameter [mm]	2038
Static radius [mm]	947
Rolling circumference [mm]	6.224
5	0.221
Payload in kg at kph (1)	7750 / 65
Payload in kg at kph (1)	7750 / 65
Payload in kg at kph (1) Inflation pressure [bar]	7750 / 65 3,60
Payload in kg at kph (1) Inflation pressure [bar] Weight [Kg]	7750 / 65 3,60 236,8
Payload in kg at kph (1) Inflation pressure [bar] Weight [Kg] Tyre content 75% [litre]	7750 / 65 3,60 236,8 466,5
Payload in kg at kph (1) Inflation pressure [bar] Weight [Kg] Tyre content 75% [litre] Stud height [mm]	7750 / 65 3,60 236,8 466,5 43,5
Payload in kg at kph (1) Inflation pressure [bar] Weight [Kg] Tyre content 75% [litre] Stud height [mm] Number of studs	7750 / 65 3,60 236,8 466,5 43,5 32x2

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.