



REIFEN 17.5 - 25
24 PR, TL, EM 936
E2 / L2

Product-No.: 10002302

Technical Information:

Tyre size	17.5 - 25
TL / TT	TL
LI / SI	24 PR
PR	24
Tread	EM 936
Manufacturer	BKT
Specification	E2/L2
Recom. Rim	14.00/1.5
Width [mm]	450
Outer diameter [mm]	1.340
Static radius [mm]	600
Rolling circumference [mm]	4060
Payload in kg at kph (1)	10000 / 10
Payload in kg at kph (2)	7700 / 30
Loadcapacity Twin Truck	7000 / 10
Inflation pressure [bar]	7,00
Weight [Kg]	127
Stud height [mm]	26,5
Zulassung	nicht notwendig
Direction bound	Yes
TRA Code	E2, L2

Hints and features:

- Rugged tyre for mobile excavators in the harshest of operating conditions
- Well-suited for road travel
- Aggressive tread pattern for high traction and good self-cleaning properties
- High level of stability in use and good handling on the road

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.