



## Hints and features:

REIFEN 650 / 65 R 42  
173 A8 / 170 D, TL, AGRISTAR 365  
ECE106, DEMO 80%, HÖHENSCHLAG

**Product-No.: 72400044**

## Technical Information:

Tyre size	650 / 65 R 42
TL / TT	TL
LI / SI	173 A8 / 170 D
Tread	Agristar 365
Manufacturer	Alliance
Recom. Rim	DW20
Permissible rim	DW20B
Width [mm]	650
Outer diameter [mm]	1935
Static radius [mm]	875
Rolling circumference [mm]	5.845
Payload in kg at kph (1)	6500 / 40
Payload in kg at kph (2)	6000 / 65
Inflation pressure [bar]	3,20
Weight [Kg]	235,2
Tyre content 75% [litre]	607,95
Stud height [mm]	58,0
Number of studs	22x2
Zulassung	ECE 106
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.