





Hints and features:

- The Sailun SAW1 is a truck winter tyre for steering axles but is also suitable for trailers
- The wide tread pattern and the tread pattern with 5 main grooves enable very good and safe handling on snow and ice
- Jagged sipes increase the contact area with the road and enhance the grip
- The sipe design and the shoulder grooves open on the sides reliably deflect water and snow
- The special rubber compound keeps its positive characteristics even at low temperatures

RAD 385 / 65 R 22.5 SAILUN SAW1, 3PMSF 20 PR, 160 K (158 L), TL, 10/281/335,M22,MZ,ET+120 11.75 X 22.5, RAL9006 SILBER, HMA 132,25, ALV

Product-No.: 10002414

Technical Information:

Wheel size	385 / 65 R 22.5
LI / PR	160 K (158 L), 20 PR
Tread	SAW1
Manufacturer	Sailun
Rim	11.75 x 22.5 H
Connection	10/281/335
Bolt hole execution	M22
Rim centering	MZ
ET	+120
Width [mm]	385
Outer diameter [mm]	1.072
Static radius [mm]	495,96
Rolling circumference [mm]	3103
Inflation pressure [bar]	9,00
Loadcapacity Tyre	4500 / 110
Loadcapacity Rim	5000 / 130
Loadcapacity compl. Wheel	4.500
Tread depth [mm]	15,0
Rolling resistance	E
Wet grip	C
Rolling Noise DB	74
Rolling Noise Level	В
Rim meterial	Stahl
RAL / Color	RAL9006 / Silber
Weight [Kg]	118,58

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.