



REIFEN VF 650 / 60 R 42
174 D, TL, AGRIMAX V-FLECTO
ECE106

Product-No.: 10002325

Technical Information:

Tyre size	VF 650 / 60 R 42
TL / TT	TL
LI / SI	174 D
Tread	Agrimax V-Flecto
Manufacturer	BKT
Recom. Rim	DW23B
Permissible rim	DW21B
Width [mm]	660
Outer diameter [mm]	1.845
Static radius [mm]	834
Rolling circumference [mm]	5564
Payload in kg at kph (1)	6700 / 65
Inflation pressure [bar]	2,40
Weight [Kg]	248,73
Stud height [mm]	56,0
Number of studs	22x2
Zulassung	ECE 106
Tyre technology	VF
Direction bound	Yes

Hints and features:

- The BKT Agrimax V-Flecto is a VF tyre of the new generation
- Compared with a standard tyre, the tyre achieves 40% more load capacity at the same inflation pressure or the same load capacity with 40% less inflation pressure
- In contrast to most VF tyres, the tyre can be mounted on a standard rim (NRO=Narrow Rim Option)
- Its 10 % larger contact area compared with a standard tyre enables outstanding traction while significantly reducing soil compaction
- The specially shaped bead (Bead Protection System) closes extremely airtight and keeps the inflation pressure constant in all conditions
- During road journeys, the particular lug angles ensure reduced vibrations and noise levels
- There is no need to adjust the inflation pressure for optimum performance both in the field and on the road
- The extremely strong polyester casing provides a 10 % longer service life in comparison with a standard tyre, even in difficult conditions

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.