





## Hints and features:

REIFEN 710 / 70 R 38 172 D, TL, AGRI STAR II ECE106, STOLLEN LEICHT BESCHÄDIGT

Product-No.: 72400072

## **Technical Information:**

Tyre size	710 / 70 R 38
TL/TT	TL
LI/SI	172 D
Tread	Agri Star II
Manufacturer	Alliance
Specification	Stubble Guard
Recom. Rim	DW23B
Permissible rim	DW25B
Width [mm]	720
Outer diameter [mm]	1959
Static radius [mm]	839
Static radius [mm] Rolling circumference [mm]	<ul><li>839</li><li>5.781</li></ul>
Rolling circumference [mm]	5.781
Rolling circumference [mm] Payload in kg at kph (1)	5.781 6300 / 65
Rolling circumference [mm] Payload in kg at kph (1) Inflation pressure [bar]	5.781 6300 / 65 2,40
Rolling circumference [mm] Payload in kg at kph (1) Inflation pressure [bar] Weight [Kg]	5.781 6300 / 65 2,40 290
Rolling circumference [mm] Payload in kg at kph (1) Inflation pressure [bar] Weight [Kg] Tyre content 75% [litre]	5.781 6300 / 65 2,40 290 432,75
Rolling circumference [mm] Payload in kg at kph (1) Inflation pressure [bar] Weight [Kg] Tyre content 75% [litre] Stud height [mm]	5.781 6300 / 65 2,40 290 432,75 61,0

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.