





Hints and features:

- Super-wide tyre for upper performance class
- Specially designed for gentle soil tillage
- Suitable for heavy road transport

REIFEN 650 / 60 R 34 159 D / 155 E, TL, MACHXBIB

Product-No.: 10002511

Technical Information:

Tyre size	650 / 60 R 34
TL / TT	TL
LI/SI	159 D / 155 E
Tread	MachXBib
Manufacturer	Michelin
Recom. Rim	DW21B (A)
Permissible rim	DW20B (A), DW23B (A)
Width [mm]	659
Outer diameter [mm]	1.664
Static radius [mm]	752
Rolling circumference [mm]	4950
Payload in kg at kph (1)	4375 / 65
Payload in kg at kph (2)	3875 / 70
Inflation pressure [bar]	2,40
Weight [Kg]	220,00
Tyre content 75% [litre]	500
Stud height [mm]	58,0
Number of studs	18x2
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.