Bohnenkamp Moving Professionals

WINDPOWER



Hints and features:

- The Boka Agrar Trans is a hot retreaded tyre with a road tread pattern
- It was retreaded in a particularly environmentally friendly process and reduces the vehicle's CO emission thanks to its low rolling resistance
- Because of its eco-friendly characteristics the tyre is marked with a circumferential green signing stripe and an engraved ECO logo

RAD 385 / 65 R 22.5 WINDPOWER WTR 69+, 3PMSF

4.500 KG - 100 KM/H, TL, 8/221/275, A3, ET 0 11.75 X 22.5, RAL9006 SILBER, ALV

Product-No.: 10002662

Technical Information:

Wheel size	385 / 65 R 22.5
LI / PR	164 K (158 L), 20 PR
Tread	WTR 69+
Manufacturer	Windpower
Rim	11.75 x 22.5
Connection	8/221/275
Bolt hole execution	A3
Rim centering	BZ
Width [mm]	384
Outer diameter [mm]	1.069
Static radius [mm]	499
Rolling circumference [mm]	3260
Inflation pressure [bar]	9,00
Loadcapacity Tyre	5000 / 110
Loadcapacity Rim	4500 / 100
Loadcapacity compl. Wheel	4.500
Tread depth [mm]	16,8
Rolling resistance	В
Wet grip	С
Rolling Noise DB	72
Rolling Noise Level	В
Rim meterial	Stahl
RAL / Color	RAL9006 / Silber
Weight [Kg]	128,45

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.