



REIFEN VF 650 / 65 R 34
167 D / 163 E, TL, EVOBIB



Product-No.: 10002713

Technical Information:

Tyre size	VF 650 / 65 R 34
TL / TT	TL
LI / SI	167 D / 163 E
Tread	EvoBib
Manufacturer	Michelin
Recom. Rim	DW23B(A)
Permissible rim	DW21B(A)
Width [mm]	679
Outer diameter [mm]	1.707
Static radius [mm]	745
Rolling circumference [mm]	5032
Payload in kg at kph (1)	5450 / 65
Payload in kg at kph (2)	4875 / 70
Inflation pressure [bar]	2,40
Weight [Kg]	241
Tyre content 75% [litre]	600
Stud height [mm]	55,0
Number of studs	23x2
Tyre technology	VF
Direction bound	Yes

Hints and features:

- The Michelin Evobib is an innovative tyre for field and road applications
- The special 2-in-1-technology enables the tyre to change its tread pattern and contact area according to the inflation pressure
- It combines the characteristics of 2 tyres and adapts perfectly to the respective operating and soil conditions
- Used in the field with an inflation pressure of less than 1.2 bar, the tyre shoulders drop
- This increases the contact area by up to 20%, traction is improved and the soil is optimally protected
- When used on the road with higher inflation pressure, the tyre shoulders are raised, only the middle part of the tread touches the ground
- This reduces rolling resistance and fuel consumption and increases the ride comfort