



REIFEN VF 650 / 60 R 34  
165 D / 161 E, TL, EVOBIB

**Product-No.: 10002714**



## Technical Information:

Tyre size	VF 650 / 60 R 34
TL / TT	TL
LI / SI	165 D / 161 E
Tread	EvoBib
Manufacturer	Michelin
Recom. Rim	DW23B(A)
Permissible rim	DW24B(A)
Width [mm]	677
Outer diameter [mm]	1.646
Static radius [mm]	705
Rolling circumference [mm]	4841
Payload in kg at kph (1)	5150 / 65
Payload in kg at kph (2)	4625 / 70
Inflation pressure [bar]	2,40
Weight [Kg]	240,00
Tyre content 75% [litre]	500
Stud height [mm]	55,0
Tyre technology	VF
Direction bound	Yes

## Hints and features:

- The Michelin Evobib is an innovative tyre for field and road applications
- The special 2-in-1-technology enables the tyre to change its tread pattern and contact area according to the inflation pressure
- It combines the characteristics of 2 tyres and adapts perfectly to the respective operating and soil conditions
- Used in the field with an inflation pressure of less than 1.2 bar, the tyre shoulders drop
- This increases the contact area by up to 20%, traction is improved and the soil is optimally protected
- When used on the road with higher inflation pressure, the tyre shoulders are raised, only the middle part of the tread touches the ground
- This reduces rolling resistance and fuel consumption and increases the ride comfort