



REIFEN VF 380 / 85 R 34  
160 D, TL, AGRIMAX SPARGO  
ECE106

**Product-No.: 10002731**

#### Technical Information:

Tyre size	VF 380 / 85 R 34
TL / TT	TL
LI / SI	160 D
Tread	Agrimax Spargo
Manufacturer	BKT
Specification	R1
Recom. Rim	W13A
Width [mm]	380
Outer diameter [mm]	1.500
Static radius [mm]	678
Rolling circumference [mm]	4514
Payload in kg at kph (1)	4500 / 65
Inflation pressure [bar]	3,20
Weight [Kg]	118,68
Stud height [mm]	34,5
Number of studs	26x2
Zulassung	ECE 106
Tyre technology	VF
Direction bound	Yes
TRA Code	R1

#### Hints and features:

- Row crop tyre with VF technology for self-propelled and towed field sprayers and tractors
- Up to 40% higher load capacity at constant inflation pressure or up to 40% lower inflation pressure with the same payload compared with standard tyres
- Excellent plant and soil protection allows yield increases
- Excellent ride comfort and high machine stability

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.