



Hints and features:

- The BKT Rock Grip is an earthmoving tyre with a 150 % tread pattern (E-4)
- The solid, heavy casing and the special tread compound prevent cuts and other damage and ensure the best possible resistance against heat development during operation
- Suitable for use on dumpers, wheel loaders and reach stackers

REIFEN 21.00 - 35 40 PR, TL, ROCK GRIP E4

Product-No.: 15772705

## **Technical Information:**

Tyre size	21.00 - 35
TL/TT	TL
LI/SI	40 PR
PR	40
Tread	Rock Grip
Manufacturer	BKT
Specification	E4
Recom. Rim	15.00/3.0
Width [mm]	580
Outer diameter [mm]	2040
Static radius [mm]	943
Rolling circumference [mm]	6068
Payload in kg at kph (1)	30375 / 25
Payload in kg at kph (2)	32800 / 10
Inflation pressure [bar]	9,90
Weight [Kg]	628,1
Stud height [mm]	59,5
Zulassung	nicht notwendig
TRA Code	E4

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.