



Hints and features:

REIFEN 650 / 65 R 42
168 A8 / 165 D, TL, AGRIMAX RT 657
DEMO 95%, UNRUHIGES FAHRVERHALTEN,
WULST BESCHÄDIGT

Product-No.: 72400111

Technical Information:

Tyre size	650 / 65 R 42
TL / TT	TL
LI / SI	168 A8 / 165 D
Tread	Agrimax RT 657
Manufacturer	BKT
Recom. Rim	DW20B
Permissible rim	TW18B
Width [mm]	645
Outer diameter [mm]	1913
Static radius [mm]	878
Rolling circumference [mm]	5810
Payload in kg at kph (1)	5600 / 40
Payload in kg at kph (2)	5150 / 65
Inflation pressure [bar]	2,40
Weight [Kg]	250
Stud width [mm]	50
Stud height [mm]	58,5
Number of studs	21x2
Zulassung	ECE 106
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.