





Hints and features:

- MPT radial tyre for compact construction machinery, such as excavators, wheel or telescopic loaders and skid steer machines
- Massive contact area for stability, in combination with wide centre lugs for hard surfaces
- High lugs in the shoulder area for traction on loose surfaces
- Optimised rolling resistance allows fuel savings

RAD 405 / 70 R 18 ALLIANCE 608 153 A2 / 141 B, TL, 8/221/275, B3, ET +40 13 X 18, RAL9006 SILBER, VS H

Product-No.: 10002942

## **Technical Information:**

Wheel size	405 / 70 R 18
LI / PR	153 A2 / 141 B
Tread	608
Manufacturer	Alliance
Rim	13 x 18
Connection	8/221/275
Bolt hole execution	B3
Rim centering	BZ
ET	+40
Width [mm]	408
Outer diameter [mm]	1025
Static radius [mm]	450
Rolling circumference [mm]	3084
Inflation pressure [bar]	4,40
Loadcapacity Tyre	3650 / 10
Loadcapacity Rim	3750 / 25
Loadcapacity compl. Wheel	3.650
Rim meterial	Stahl
RAL / Color	RAL9006 / Silber
Weight [Kg]	90,05

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.