Bohnenkamp Moving Professionals

MICHELIN



Hints and features:

- The Michelin Axiobib 2 is designed for tractors within a performance range of 60 to 170 hp
- The new optimised tread with a lug angle of 45° offers very good traction transmission to the ground
- Its particularly high tread depth ensures a long service life for the tyre
- Thanks to the additional rubber lip along the tread centre, the tyre offers very good self-cleaning properties
- The angle of the lugs and a rubber reinforcement on the tyre shoulder deflect stubble and protect the tyre from damage

REIFEN 420 / 85 R 30 145 A8 / 139 D, TL, AGRIBIB 2

Product-No.: 10002869

Technical Information:

Tyre size	420 / 85 R 30
TL/TT	TL
LI / SI	145 A8 / 139 D
Tread	AgriBib 2
Manufacturer	Michelin
Recom. Rim	DW15L
Permissible rim	DW14L, W14L, W15L
Width [mm]	446
Outer diameter [mm]	1487
Static radius [mm]	667
Rolling circumference [mm]	4416
Payload in kg at kph (1)	2900 / 40
Payload in kg at kph (2)	2430 / 65
Inflation pressure [bar]	2,40
Weight [Kg]	95
Tyre content 75% [litre]	270
Stud height [mm]	52,0
Number of studs	21x2
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential

damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.