Bohnenkamp Moving Professionals

BKT



Hints and features:

- Steel belted flotation tyre for versatile applications on a wide range of agricultural vehicles and trailers
- Enormous load capacity and high transport performance due to 65 km/h approval (in some cases even 70 km/h)
- Modern, directional tread pattern for very good road characteristics as well as cleaning properties when used in fields
- Low rolling resistance allows fuel savings

REIFEN 650 / 65 R 30.5 176 D, TL, RIDEMAX FL 693 M ECE106

Product-No.: 10002969

Technical Information:

Tyre size	650 / 65 R 30.5
TL/TT	TL
LI / SI	176 D
Tread	Ridemax FL 693 M
Manufacturer	ВКТ
Recom. Rim	AG20.00
Width [mm]	645
Outer diameter [mm]	1623
Static radius [mm]	734
Rolling circumference [mm]	4939
Payload in kg at kph (1)	7100 / 65
Inflation pressure [bar]	4,00
Weight [Kg]	197,47
Stud height [mm]	24,5
Zulassung	ECE 106
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.