





Hints and features:

- The Alliance FarmPro 324 has a modern 45 degree lug angle design, suitable for field and road applications
- In field use, the tyre is characterised by very good traction
- The revised, new-look tread pattern provides excellent self-cleaning properties
- Its particularly resistant rubber compound prevents the enlargement of minor punctures
- The complete R-1 range is available with this tread pattern

REIFEN 6.00 - 16 8 PR, 94 A6, TT, FARMPRO 324 ECE106

Product-No.: 10002682

Technical Information:

Tyre size	6.00 - 16
TL / TT	TT
LI/SI	94 A6
PR	8
Tread	FarmPRO 324
Manufacturer	Alliance
Specification	R1
Recom. Rim	4.5E
Width [mm]	165
Outer diameter [mm]	735
Static radius [mm]	349,1
Rolling circumference [mm]	2172
Payload in kg at kph (1)	670 / 30
Inflation pressure [bar]	4,50
Weight [Kg]	9,6
Tyre content 75% [litre]	21,53
Stud height [mm]	18,0
Number of studs	18x2
Zulassung	ECE 106
Direction bound	Yes
TRA Code	R1

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.